

# SAFETY DATA SHEET

According to Regulation ( EC ) No. 1907 / 2006

Form Number  
ET900BBP-\*

Substance / Mixture Name  
900BBP  
TEXTURED BUMPER  
BLACK PAINT

Printing Date  
Revision Date  
Revision No

07.2012  
15.12.2016  
2

## SECTION 1 • IDENTIFICATION OF THE SUBSTANCE/MIXTURE/AND OF THE COMPANY/UNDERTAKING

---

### 1.1- Product identifier:

Product Name            900BBP TEXTURED BUMPER BLACK PAINT  
Product Code            ET900BBP-\*

### 1.2- Product Description:

1K textured paint for plastic parts of vehicles, especially for bumpers. Different texture can be achieved by adjusting air pressure of spray gun and by varying the distance between spray gun and surface.

### 1.3- Details of the supplier of the safety data sheet:

ETALON is a brand of Alexport Company.  
Pontou 26, P.C. 546 28, Thessaloniki, Greece,  
Tel: +30 2310 501814, Fax: +30 2310 524 771  
info@alexport.gr, www.alexport.gr  
www.etalon-refinish.com

1.4- Emergency phone number    122 or call your doctor/local poison center

## SECTION 2 • HAZARDS IDENTIFICATION

---

### 2.1- Classification of the substance or mixture:

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS].

**Physical Hazards**            Flammable liquids, Category 3


**Health Hazards**            Causes skin irritation, Category 2  
   Causes eye irritation, Category 2  
   Specific target organ toxicity – single exposure, Category 3

**Environmental Hazards**    None known.

Classification according to Regulation (EC) No. 1272 / 2008

## 2.2- Label elements:

### Hazard pictograms



Signal word : Danger

### Hazard Statements

<b>H226</b>	Flammable liquid and vapour
<b>H319</b>	Causes serious eye irritation.
<b>H315</b>	Causes skin irritation.
<b>H336</b>	May cause drowsiness or dizziness
<b>EUH066</b>	Repeated exposure may cause skin dryness or cracking

### Precautionary statements

<b>P210</b>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
<b>P241</b>	Use explosion-proof electrical/ventilating/light/.../equipment.
<b>P243</b>	Take precautionary measures against static discharge.
<b>P264</b>	Wash contacted areas thoroughly after handling.
<b>P270</b>	Do not eat, drink or smoke when using this product.
<b>P271</b>	Use only outdoors or in a well-ventilated area.
<b>P280</b>	Wear protective gloves/protective clothing/eye protection/face protection

### Response precautionary statements

<b>P304+P340</b>	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
<b>P301+P310</b>	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
<b>P303+P361+P353</b>	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
<b>P305+P351+P338</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.

### Storage precautionary statements

<b>P405</b>	Store locked up.
<b>P403+P233</b>	Store in a well-ventilated place. Keep container tightly closed.

# SAFETY DATA SHEET

According to Regulation ( EC ) No. 1907 / 2006

Form Number  
ET900BBP-\*

Substance / Mixture Name  
900BBP  
TEXTURED BUMPER  
BLACK PAINT

Printing Date  
Revision Date  
Revision No

07.2012  
15.12.2016  
2

## SECTION 3 • COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Concentration	CAS No	EC No	Classification 1272/2008 (CLP)
Ethyl acetate	%10-20	141-76-2	205-500-4	Flammable Liquid 2 H225, STOT Single exposure 3 H336, Eye irritation 2 H319
Xylene Acute	%10-15	1330-20-7	215-535-7	Flammable liquid 3 H226,  Tox. 4 H332, H312, Skin Irrit. 2; H315
Butyl acetate	%10-20	123-86-4	204-658-1	Flammable Liquid 3 H226, STOT Single exposure 3 H336

## SECTION 4 • FIRST AID MEASURES

### 4.1 Description of first aid measures

- In case of eye contact** : Remove contact lenses, keep eyelids open for at least 10 minutes, flush with plenty of clean water and seek immediate medical attention.
- If inhaled** : Move to fresh air. If person is not breathing, provide artificial respiration. If breathing is irregular or if respiratory arrest occurs, provide oxygen. Seek immediate medical attention.
- In case of skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvent or thinners.
- If swallowed** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting. Provide plenty of water for the person to drink and stay with him/her.

### 4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly

#### **4.3 Indication of any immediate medical attention and special treatment needed**

**Specific treatments** : No specific treatment.

---

### **SECTION 5 • FIREFIGHTING MEASURES**

---

#### **5.1 Extinguishing media**

**Suitable extinguishing media** : Recommended: alcohol-resistant foam, Powders, Carbon dioxide (CO<sub>2</sub>)

**Unsuitable extinguishing media** : Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions

#### **5.2 Special hazards arising from the substance or mixture**

**Hazards from the substance or mixture** : Do not breathe combustion products. Exposure of containers to fire can create an extreme pressure which can cause explosion hazard

#### **5.3 Advice for firefighters**

**Special protective equipment for firefighters** : Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations. Suitable respiratory equipment, protective clothing, protective gloves may be required.

---

### **SECTION 6 • ACCIDENTAL RELEASE MEASURES**

---

#### **6.1 Personal precautions, protective equipment and emergency procedures**

Avoid contact with skin and eyes. Wear suitable protective equipment (personal protective equipment listed in section 8 of the safety data sheet). Keep away from sources of ignition. Ensure adequate ventilation. This information applies to both staff working on emergency interventions.

#### **6.2 Environmental precautions**

If any spillage occurs, clean it immediately using absorbent material. Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system.

#### **6.3 Methods and materials for containment and cleaning up**

# SAFETY DATA SHEET

According to Regulation ( EC ) No. 1907 / 2006

Form Number  
ET900BBP-\*

Substance / Mixture Name  
900BBP  
TEXTURED BUMPER  
BLACK PAINT

Printing Date  
Revision Date  
Revision No

07.2012  
15.12.2016  
2

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Prefer cleaning with detergent. Avoid using solvents.

## 6.4 Reference to other sections

See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7 • HANDLING AND STORAGE

---

### 7.1 Handling

#### Precautions for safe handling

: Use earthing leads when transferring from one container to another. Operators should wear anti-static footwear and clothing and floors should be electrically conductive. Exclude sources of heat, sparks and open flame. Use only non-sparking tools. Avoid contact with eyes and skin. Avoid the inhalation of dust, particulates and spray mist arising from the application of this preparation. Smoking, eating and drinking should be prohibited in areas of storage and use.

#### 7.2 Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Keep away from: oxidizing agents, strong alkalis, strong acids. Observe label precautions. Store in closed original container at temperatures between 5°C and 30°C. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking. Prevent unauthorized access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

### 7.3 Specific end use(s)

Recommendations : Not available

## SECTION 8 • EXPOSURE CONTROLS / PERSONAL PROTECTION

---

### 8.1 Control parameters

#### Occupational exposure limits

Ingredient name	Type	Exposure limit values			
		TWA (8 hrs.)			
		mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm
xylene	OEL	221	50	442	100
Ethyl acetate	TLV	-	400	-	-
butyl acetate	TLV	713	150	950	200

## 8.2. Exposure controls

### Appropriate engineering controls

: Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction.

If these are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn.

### Individual protection Measures

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn: Chemical splash goggles. Recommended: Use protective goggles with side shields. Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.



### Environmental exposure Controls

: Do not allow to enter drains or watercourses.

# SAFETY DATA SHEET

According to Regulation ( EC ) No. 1907 / 2006

Form Number  
ET900BBP-\*

Substance / Mixture Name  
900BBP  
TEXTURED BUMPER  
BLACK PAINT

Printing Date  
Revision Date  
Revision No

07.2012  
15.12.2016  
2

## SECTION 9 • PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

Appearance	: Liquid
Color	: Black
Odor	: Characteristic
Ph	: Not available
Melting point / range	: Not available
Flash point	: 27 °C
Flammability (solid, gas)	: Not available
Explosive properties	: Not available
Oxidizing properties	: Not available
Vapor pressure	: Not available
Relative density solubility	: 1,20 ± 0,1 g/ml
- in the water	: Partially
- in the oil (solvent oil indicated)	: Insoluble
Partition coefficient: n-octanol/water	: Not available.
Dynamic viscosity	: 1000-2000 cP
Vapor density	: Not available.
Evaporation rate	: Not available.
VOC	: 475 g/l

## SECTION 10 • STABILITY AND REACTIVITY

**10.1 Reactivity** : No specific test data related to reactivity available for this product.

**10.2 Chemical stability** : Stable under recommended storage and handling conditions (see Section 7).

**10.3 Possibility of hazardous reactions** : May react with strong oxidizers.

**10.4 Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products

**10.5 Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids

**10.6 Hazardous decompositions products** : In the event of thermal decomposition or fire, gases and vapours that potentially dangerous to health may be released.

## SECTION 11 • TOXICOLOGICAL INFORMATION

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

If splashed in the eyes, the liquid may cause irritation and reversible damage. May cause an allergic skin reaction. Inhalation of vapor may cause respiratory irritation.

Product may cause dizziness, drowsiness, loss of reflex.

### Acute toxicity

butyl acetate	LD50 (Oral)	10760 mg/kg Rat
	LD50 (Dermal)	>14112 mg/kg Rabbit
	LC50 (Inhalation)	23,4 mg/4h Rat
xylene	LD50 (Oral)	3523 mg/kg Rat
	LD50 (Dermal)	4350 mg/kg Rabbit
	LC50 (Inhalation)	6350 ppm/4h Rat

### Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure
Butyl acetate Ethyl acetate	Category 3	Inhalation

## SECTION 12 • EKOLOGICAL INFORMATION

### 12.1 Ecotoxicity

There are no data available on the mixture itself  
Do not allow to enter drains or watercourses.

### 12.2 Persistence and degradability

**Conclusion/Summary** : Not available

### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	Potential
Xylene	3.12	Low
butyl acetate	2.3	Low

### 12.4 Mobility in soil

**Soil/water partition coefficient (KOC)** : Not available

**Mobility** : Not available



# SAFETY DATA SHEET

According to Regulation ( EC ) No. 1907 / 2006

Form Number  
ET900BBP-\*

Substance / Mixture Name  
900BBP  
TEXTURED BUMPER  
BLACK PAINT

Printing Date  
Revision Date  
Revision No

07.2012  
15.12.2016  
2

## 12.5 Results of PBT and vPvB assessment

PBT : Not applicable.  
vPvB : Not applicable.

12.6 Other adverse effects : No known significant effects or critical hazards

## SECTION 13 • DISPOSAL CONSIDERATIONS

---




### 13.1 Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Disposal must be performed through an authorized waste management firm, in compliance with national and local regulations. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. Dispose of containers contaminated by the product in accordance with local or national legal provisions. Waste transportation may be subject to ADR restrictions.

## SECTION 14 • TRANSPORT INFORMATION

---

UN No	ADR/RID	IMDG	IATA
	1263	1263	1263

UN proper shipping name	PAINT	PAINT	PAINT
Transport hazard class(es)	3 Flammable liquids 	3 Flammable liquids 	3 Flammable liquids 
Packing group	III	III	III
Environmental hazards	No.	No.	No.
Special precautions for user	<u>Special Provision</u> 163-640E  <u>Limited Quantities</u> 5L  <u>Excepted quantities Code</u> E1  <u>Tunnel Restriction Code</u> D/E	<u>EmS Fire Codes</u> F-E  <u>EmS Spill Codes</u> S-E	

## SECTION 15 • REGULATORY INFORMATION

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

**Seveso Directive** : This product has been controlled under the Seveso Directive.  
**Seveso Category** : Category 6

This product has been controlled under the Directive 2009/161/EU - indicative occupational exposure limit values.  
This product has been prepared under the Regulation ( EC ) No. 1907 / 2006

**EU Regulation (EC) No. 1907/2006 (REACH)** : None of the components are listed.  
**Annex XIV - List of substances subject to authorization**  
**Annex XIV**

**Substances of very high concern** : None of the components are listed.

**Annex XVII – Restrictions on the manufacture placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

**Stockholm Convention on Persistent Organic Pollutants** : Not listed  
**Rotterdam Convention on Prior Inform Consent (PIC)** : Not listed

**Montreal Protocol (Annexes A, B, C, E)** : Not listed

### 15.2 Chemical safety assessment

For this substance a chemical safety assessment is not required.

# SAFETY DATA SHEET

According to Regulation ( EC ) No. 1907 / 2006

Form Number  
ET900BBP-\*

Substance / Mixture Name  
900BBP  
TEXTURED BUMPER  
BLACK PAINT

Printing Date  
Revision Date  
Revision No

07.2012  
15.12.2016  
2

## SECTION 16 • OTHER INFORMATION

Revision No : 2

### Key to abbreviations:

<b>ADR:</b>	European Agreement concerning the International Carriage of Dangerous Goods by Road
<b>CAS NUMBER</b>	: Chemical Abstracts Service
<b>CLP</b>	: Classification, labeling and packaging Regulation (CE) 1272/2008
<b>EUH STATEMENT</b>	: CLP-specific Hazard statement
<b>LD50</b>	: Lethal dose, 50 percent
<b>LC50</b>	: Lethal concentration, 50 percent
<b>INDEX NUMBER</b>	: Table 3.1 of Annex VI to the CLP Regulation.
<b>ECHA</b>	: European Chemicals Agency
<b>vPvB</b>	: Very persistent and very bioaccumulative
<b>PBT</b>	: Persistent, bioaccumulative and toxic
<b>OEL</b>	: Occupational exposure limit
<b>REACH</b>	: Regulation (EC) No 1907/2006
<b>TWA STEL</b>	: <u>Short-term exposure limits</u>
<b>TWA</b>	: Time – weighted average exposure limits
<b>IATA DGR</b>	: International Air Transport Association-Dangerous Goods Regulations
<b>IMDG</b>	: International Maritime Code for Dangerous Goods
<b>ATE</b>	: Acute Toxicity Estimate

### Relevant phrases:

H226	Flammable liquid and vapour
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness
EUH066	Repeated exposure may cause skin dryness or cracking

### Full text of classifications [CLP/GHS]:

Flam. Liq. 3	H226	Flammable liquids – Category 3
Eye Irrit. 2	H319	Eye corrosion/irritation - Category 2
Skin Irrit. 2	H315	Skin corrosion/irritation - Category 2
STOT SE 3	H336	Specific target organ toxicity (Single exposure) (Narcotic effects) - Category 3

--	--

**Further information:**

The information in this Safety Data Sheet is based on the present state of knowledge and current legislation. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.