



MARINE ENGINE PAINT SPRAY

VOLVO PENTA GREEN	CATERPILLAR YELLOW
YANMAR GREY METALLIC	HONDA MARINE GREY METALLIC
SUZUKI BLACK METALLIC	JOHNSON GREY METALLIC
YAMAHA DARK GREY METALLIC	SUZUKI GREY METALLIC
YAMAHA WHITE	JOHNSON EVINRUDE WHITE
MERCURY BLACK	YAMAHA BLUISH GREY MET



Product

Fast drying premium quality acrylic paint with a direct adhesion on PVC. Specially suited for the spot repair of machines, machinery parts, tools, vehicles and much more. Can be overcoated with acrylic clearcoat for better protection and shine.

Substrates

Suitable for fully hardened and sanded old paint work, dry 1K & 2K filler materials and PVC.



Surface Preparation

Scuff with non-woven abrasive, clean and degrease.



Application Conditions

From +10°C and up to 80% relative air humidity. Shake the can vigorously until the mixing ball moves freely.



Number of Layers

2-3 coats at 20-30cm distance.



Flash off

3-5 min

Coating Thickness

40-50µm



Drying

Dust free at 10min at 20°C.
Set to touch at 1-2hours at 20°C.
Full hardness at 12hours at 20°C.



Cleaning of equipment

After the application turn the can upside down and press the nozzle for 5sec.

Shelf life

5 years