

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 01.07.2022



Version number 6 (replaces version 5)

Revision: 02.06.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** ETALON EPOXY PRIMER SPRAY DARK GREY 500 ML
- **Article number:** ETL002
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Sector of Use**
SU21 Consumer uses: Private households / general public / consumers
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Product category** Paint remover
- **Process category**
PROC7 Industrial spraying
PROC11 Non industrial spraying
- **Application of the substance / the mixture** Spray varnish
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
ETALON is a brand of Alexport Company.
Pontou 26, P.C. 546 28, Thessaloniki, Greece,
Tel: +30 2310 501814, Fax: +30 2310 524 771
info@alexport.gr, www.alexport.gr
www.etalon-refinish.com
- **Further information obtainable from:**
- **1.4 Emergency telephone number:**
122 or call your local doctor/poison center

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
- | | | |
|---|-----------|--|
|  | flame | |
| Aerosol 1 | H222-H229 | Extremely flammable aerosol. Pressurised container: May burst if heated. |
- | | | |
|---|------|------------------------------------|
|  | | |
| Eye Irrit. 2 | H319 | Causes serious eye irritation. |
| STOT SE 3 | H336 | May cause drowsiness or dizziness. |
- | | | |
|-------------------|------|--|
| Aquatic Chronic 3 | H412 | Harmful to aquatic life with long lasting effects. |
|-------------------|------|--|
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 01.07.2022

Version number 6 (replaces version 5)

Revision: 02.06.2022

Trade name: ETALON EPOXY PRIMER SPRAY DARK GREY 500 ML

(Contd. of page 1)

· Hazard pictograms



GHS02 GHS07

· Signal word *Danger*

· Hazard-determining components of labelling:

acetone
propan-2-ol
iso-butanol

· Hazard statements

H222-H229 *Extremely flammable aerosol. Pressurised container: May burst if heated.*
H319 *Causes serious eye irritation.*
H336 *May cause drowsiness or dizziness.*
H412 *Harmful to aquatic life with long lasting effects.*

· Precautionary statements

P101 *If medical advice is needed, have product container or label at hand.*
P102 *Keep out of reach of children.*
P210 *Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.*
P211 *Do not spray on an open flame or other ignition source.*
P251 *Do not pierce or burn, even after use.*
P260 *Do not breathe spray.*
P410+P412 *Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.*
P501 *Dispose of contents / container in accordance with regional regulations.*

· Additional information:

EUH066 *Repeated exposure may cause skin dryness or cracking.*
Buildup of explosive mixtures possible without sufficient ventilation.
EUH211 *Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.*

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

* SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37	dimethyl ether ⚠ Flam. Gas 1A, H220 Press. Gas (Comp.), H280	25-<50%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49	acetone ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	25-<50%

(Contd. on page 3)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 01.07.2022

Version number 6 (replaces version 5)

Revision: 02.06.2022

Trade name: ETALON EPOXY PRIMER SPRAY DARK GREY 500 ML

(Contd. of page 2)

CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32	xylene, mixture of isomers ⚠ Flam. Liq. 3, H226 ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	5-<10%
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25	propan-2-ol ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	5-<10%
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2 Reg.nr.: 01-2119489379-17	titanium dioxide ⚠ Carc. 2, H351	<2.5%
CAS: 78-83-1 EINECS: 201-148-0 Index number: 603-108-00-1 Reg.nr.: 01-2119484609-23	iso-butanol ⚠ Flam. Liq. 3, H226 ⚠ Eye Dam. 1, H318 ⚠ Skin Irrit. 2, H315; STOT SE 3, H335-H336	<2.5%
CAS: 1314-13-2 EINECS: 215-222-5 Index number: 030-013-00-7 Reg.nr.: 01-2119463881-32	zinc oxide ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	<1%

Additional information:

Note C (Regulation (EC) no. 1272/2008) applies to the component Xylene (mixture) CAS: 1330-20-7.
For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
- **5.2 Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters -**
- **Protective equipment:** Mouth respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Ensure adequate ventilation
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
Keep away from ignition sources.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 01.07.2022

Version number 6 (replaces version 5)

Revision: 02.06.2022

Trade name: ETALON EPOXY PRIMER SPRAY DARK GREY 500 ML

(Contd. of page 3)

- **6.2 Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 2 B
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm
Long-term value: 766 mg/m³, 400 ppm

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm
Long-term value: 1210 mg/m³, 500 ppm

1330-20-7 xylene, mixture of isomers

WEL Short-term value: 441 mg/m³, 100 ppm
Long-term value: 220 mg/m³, 50 ppm
Sk; BMGV

67-63-0 propan-2-ol

WEL Short-term value: 1250 mg/m³, 500 ppm
Long-term value: 999 mg/m³, 400 ppm

13463-67-7 titanium dioxide

WEL Long-term value: 10* 4** mg/m³
*total inhalable **respirable

78-83-1 iso-butanol

WEL Short-term value: 231 mg/m³, 75 ppm
Long-term value: 154 mg/m³, 50 ppm

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 01.07.2022

Version number 6 (replaces version 5)

Revision: 02.06.2022

Trade name: ETALON EPOXY PRIMER SPRAY DARK GREY 500 ML

(Contd. of page 4)

· Ingredients with biological limit values:

1330-20-7 xylene, mixture of isomers

BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
------	--

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls** No further data; see item 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Avoid contact with the eyes.

· **Respiratory protection:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

· **Hand protection**



Protective gloves

· **Material of gloves**

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· **Penetration time of glove material**

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min

Butyl acetate: 60 min

Ethyl acetate: 170 min

Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42- 480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

· **Eye/face protection**



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Physical state**

Aerosol

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 01.07.2022

Version number 6 (replaces version 5)

Revision: 02.06.2022

Trade name: ETALON EPOXY PRIMER SPRAY DARK GREY 500 ML

(Contd. of page 5)

· Colour:	Grey
· Odour:	Solvent-like
· Odour threshold:	Not determined.
· Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and boiling range	Not applicable, as aerosol.
· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	2.6 Vol % (67-64-1 acetone)
· Upper:	26.2 Vol % (115-10-6 dimethyl ether)
· Flash point:	Not applicable, as aerosol.
· Ignition temperature:	240 °C (464 °F)
· Decomposition temperature:	Not determined.
· pH	Mixture is non-soluble (in water).
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic:	Not determined.
· Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure at 20 °C (68 °F):	4000 hPa (3000.2 mm Hg)
· Density and/or relative density	
· Density at 20 °C (68 °F):	0.8 g/cm ³ (6.7 lbs/gal)
· Relative density	Not determined.
· Vapour density	Not determined.

· **9.2 Other information**

· Appearance:	
· Form:	Aerosol
· Important information on protection of health and environment, and on safety.	
· Explosive properties:	Not determined.
· Solvent content:	
· Organic solvents:	83.8 %
· VOC (EC)	---
	683.4 g/l
· VOC-EU%	83.84 %
· Solids content:	16.0 %
· Change in condition	
· Evaporation rate	Not applicable.

· **Information with regard to physical hazard classes**

· Explosives	Void
· Flammable gases	Void
· Aerosols	Extremely flammable aerosol. Pressurised container: May burst if heated.
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 01.07.2022

Version number 6 (replaces version 5)

Revision: 02.06.2022

Trade name: ETALON EPOXY PRIMER SPRAY DARK GREY 500 ML

(Contd. of page 6)

- | | |
|----------------------------------|------|
| · Organic peroxides | Void |
| · Corrosive to metals | Void |
| · Desensitised explosives | Void |

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity**

- **LD/LC50 values relevant for classification:**

67-64-1 acetone

Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	>15800 mg/kg (rabbit)
Inhalative	LC50 / 4h	76 mg/l (rat)

1330-20-7 xylene, mixture of isomers

Oral	LD50	3523 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50 / 4 h	29000 mg/m ³ (rat)

67-63-0 propan-2-ol

Oral	LD50	5840 mg/kg (rat)
Dermal	LD50	13900 mg/kg (rabbit)
Inhalative	LC50	>25 mg/l (rat) LC 50: 6h

- **Skin corrosion/irritation** No irritant effect.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** No sensitising effects known.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

115-10-6 dimethyl ether

EC50 / 96 h	155 mg/l (algae)
LC50 / 48 h	>4000 mg/l (daphnia magna)
LC50 / 96 h	>4000 mg/l (fish)

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 01.07.2022

Version number 6 (replaces version 5)

Revision: 02.06.2022

Trade name: ETALON EPOXY PRIMER SPRAY DARK GREY 500 ML

(Contd. of page 7)

67-64-1 acetone

LC50/96h	8300 mg/l (fish)
EC50/96h	7200 mg/l (algae)
LC50 / 48 h	8450 mg/l (crustacean (water flea))

1330-20-7 xylene, mixture of isomers

EC50 / 48 h	7.4 mg/l (daphnia magna)
LC50 / 96 h	13.5 mg/l (fish)

67-63-0 propan-2-ol

LC50/96h	9640 mg/l (pimephales promelas; 96h)
LC50 / 24 h	9714 mg/l (daphnia magna)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:**
Disposal must be made according to official regulations.
Disposal must be made according to official regulations.

SECTION 14: Transport information

- | | |
|---------------------------------------|---------------------|
| · 14.1 UN number or ID number | |
| · ADR, IMDG, IATA | UN1950 |
| · 14.2 UN proper shipping name | |
| · ADR | 1950 AEROSOLS |
| · IMDG | AEROSOLS |
| · IATA | AEROSOLS, flammable |

(Contd. on page 9)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 01.07.2022

Version number 6 (replaces version 5)

Revision: 02.06.2022

Trade name: ETALON EPOXY PRIMER SPRAY DARK GREY 500 ML

(Contd. of page 8)

· 14.3 Transport hazard class(es)

· ADR



· Class 2.1F Gases.
· Label 2.1

· IMDG, IATA



· Class 2.1 Gases.
· Label 2.1

· 14.4 Packing group

· ADR, IMDG, IATA not regulated

· 14.5 Environmental hazards: Not applicable.

· 14.6 Special precautions for user

· Hazard identification number (Kemler code):

· EMS Number:

· Stowage Code

Warning: Gases.

-

F-D,S-U

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

· Segregation Code

SG69 For AEROSOLS with a maximum capacity of 1 litre:

Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.

For AEROSOLS with a capacity above 1 litre:

Segregation as for the appropriate subdivision of class 2.

For WASTE AEROSOLS:

Segregation as for the appropriate subdivision of class 2.

· 14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ)

1L

· Excepted quantities (EQ)

Code: E0

Not permitted as Excepted Quantity

· Transport category

2

· Tunnel restriction code

D

· IMDG

· Limited quantities (LQ)

1L

(Contd. on page 10)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 01.07.2022

Version number 6 (replaces version 5)

Revision: 02.06.2022

Trade name: ETALON EPOXY PRIMER SPRAY DARK GREY 500 ML

(Contd. of page 9)

- | | |
|---|---|
| <ul style="list-style-type: none"> · Excepted quantities (EQ) | <p>Code: E0
Not permitted as Excepted Quantity</p> <p>Code: E0
Not permitted as Excepted Quantity</p> |
| <ul style="list-style-type: none"> · UN "Model Regulation": | <p>UN 1950 AEROSOLS, 2.1</p> |

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P3a** FLAMMABLE AEROSOLS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **LIST OF SUBSTANCES SUBJECT TO AUTHORISATION (UK ANNEX XIV)**

- **Regulation (EC) No 273/2004 on drug precursors**

67-64-1 acetone	3
-----------------	---

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

- **Department issuing SDS:** R&D legislation and regulatory advisor

- **Contact:** e-mail: sds-nl@european-aerosols.com

· **Abbreviations and acronyms:**

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- ICAO: International Civil Aviation Organisation
- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 01.07.2022

Version number 6 (replaces version 5)

Revision: 02.06.2022

Trade name: ETALON EPOXY PRIMER SPRAY DARK GREY 500 ML

(Contd. of page 10)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

*** Data compared to the previous version altered.**

GB